



Description

The FP-1550-2-2.5-xx series of Multi-Quantum Well (MQW) Fabry-Perot (FP) lasers have been designed specifically to satisfy the requirements of Intermediate and Short-reach digital transmission systems.

The devices are cost effective solutions for transmission of high-speed data up to 2.5 Gbps. Their uncooled, hermetically sealed, coaxial fiber-pigtailed packages are provided with an integral single-mode optical fiber and a wide variety of connector options.

Features

- ❑ Advanced Multiple Quantum Well (MQW) Fabry-Perot Laser Design
- ❑ High-speed up to 2.5 Gbps
- ❑ Engineered Specifically for SONET transmitter applications
- ❑ Low-Cost Uncooled Laser Technology
- ❑ 1-meter SMF-28 Fiber Pigtail
- ❑ 5.6-mm TO-style package

Applications

- ❑ SONET 2.5 Gbps transmitter
- ❑ Intermediate and short-distance fiber-optic transmitter





FP-1550-C5-2-2.5-xx-x-x-x

Absolute Maximum Ratings

Parameter	Symbol	Condition	Min	Max	Unit
Operating Case Temperature	T_c	$I=I_{op}$	-20	85	°C
Storage Temperature	T_{sta}	--	-40	100	°C
Laser Forward Current	I_f	--	--	120	mA
Laser Reverse Bias	V_r	--	--	2	V
Photodiode Reverse Bias	V_{rpd}	--	--	10	V

Electrical and Optical Characteristics

Parameters are over operating temperature range unless otherwise noted.


Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions
Operating Temperature	T	-20	--	85*	°C	
Optical Output Power	P_o	2.0	--	--	mW	CW
Threshold Current	I_{th}	--	12 25	14 35	mA	T=25 °C T=85 °C
Forward Voltage	V_f	--	1.1	1.6	V	$P_o=2.0$ mW
Modulation Current	I_{mod}	13 10	20 --	33 50	mA	$P_o=2.0$ mW, T=25 °C $P_o=2.0$ mW,
Slope Efficiency	SE	50 30	-- --	125 200	μW/mA	CW, $P_o=2.0$ mW, T=25 °C CW, $P_o=2.0$ mW
Center Wavelength	λ_c	1520	--	1580	nm	$P_o=2.0$ mW, CW, T=25 °C
RMS Spectral Width	$\Delta\lambda$	--	1.6	2.5	nm	$P_o=2.0$ mW
Wavelength temperature coefficient	$\Delta\lambda / \Delta T$	--	0.65	0.7	nm/°C	
Rise/Fall Times	t_R, t_F	--	--	0.1	ns	$P_{peak}=2.0$ mW, 20% to 80%
Relaxation Oscillation Frequency	f_R	--	4.5	--	GHz	$P_o=2.0$ mW
Monitor Current	I_{mon}	25	--	375	μA/mW	$V_{rpd}=5$ V
Monitor Dark Current	I_D	10	--	200	nA	$V_{rpd}=5$ V
Optical Isolation**	ISO	30	--	--	dB	CW
Tracking Error	γ	-1	--	1	dB	$I_{mon}=const, \gamma=10 \log (P_o/2.0)$ [dB]

* See Ordering Options for available temperature ranges.

** Optical Isolation only applies if the single-stage optical isolator option is ordered.


FP-1550-C5-2-2.5-xx-x-x-x

Dimensions



Ordering Options

FP-1550-C5-2-2.5-xx-x-x-x



Safety Information

All versions of this laser are Class 1M laser products per IEC¹/EN² 60825-1:2001-08. Users should observe safety precautions such as those recommended by ANSI³ Z136.1-2000, ANSI Z36.2-1997 and IEC 60825-1:2001-08.

Notes about Laser Safety Class:

The Food and Drug Administration's Center for Devices and Radiological Health (FDA/CDRH) in the USA has decided to harmonize their requirements with 21 CFR 1040.10 and 1040.11 with the IEC/EN 60825-1 and IEC/EN 60601-2-22 standards. This process has not yet happened and in the interim, the CDRH agency has released '[Laser Notice No.50](#)' to reduce the regulatory burden. This notice allows IEC/EN classification and labeling of lasers within the USA.

IEC¹/EN² 60825-1 Laser Class

Class 1M: laser is safe for all conditions of use except when passed through magnifying optics such as microscopes and telescopes. Class 1M lasers produce large-diameter beams, or beams that are divergent. The MPE for a Class 1M laser cannot normally be exceeded unless focusing or imaging optics are used to narrow the beam. If the beam is refocused, the hazard of Class 1M lasers may be increased and the product class may be changed. A laser can be classified as Class 1M if the total output power is below (IEC/EN) class 3B but the power that can pass through the pupil of the eye is within Class 1.

FDA Laser Class

Class IIIB: moderate power lasers (cw: 5-500 mW, pulsed: 10 J/cm² or the diffuse reflection limit, whichever is lower). In general Class IIIB lasers will not be a fire hazard, nor are they generally capable of producing a hazardous diffuse reflection. Specific controls are recommended.

This product does not conform to 21 CFR 1040.10 and 1040.11. Consequently, this laser module is only intended for use as a component by manufacturers of electronic products and equipment.

Wavelength = 1270 – 1610 nm
Maximum Power = 75mW
Single-mode fiber pigtail
Fiber Numerical Aperture = 0.14

Labeling is not affixed to the laser module due to size constraints; rather, labeling is placed on the outside of the shipping box.

This product is not shipped with a power supply.

Caution: use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.



classified in accordance with IEC 60825-1: 2001-08

(1) IEC is a registered trademark of the International Electrotechnical Commission

(2) Within Europe the IEC standard has been adopted as a European Normative standard known as EN 60825, and each European country will have its own version of this standard, for example, the British Standards version known as BS EN 60825. There can be small differences between the different countries versions of EN 60825, and these are in part caused by the process of translating the standard into the native language of that country.

(3) ANSI is a registered trademark of the American National Standards Institute.